Räätälöitävä OTP-applikaattorimuotti vaaka-/pysty JW-AP12

Model No. JW-AP12



SPECIFICATIONS

Puristusmuotit	Vaaka- ja pystysuorat
Pakkaus	Alle 30 kg (laatikkolaatikot), 30–200 kg (vientipuulaatikot), yli 200 kg (kuplakalvo ja PE-kalvo)

JW-AP12 on OTP-applikaattorimuotti JST-liittimen puristuskoneisiin, toimitettuna sekä vaaka- että pystyversiona. Se kattaa OTP U-muotoiset avoholkilliset liittimet ja esieristetyn nylonrengasliittimen.

Molemmat versiot jakavat muotin rungon, liitinistukan ja kiinnityksen, ja eroavat siinä suunnassa, johon isku sulkeutuu: vaakasuora sivulta sulkeutuvalle asemalle, pystysuora ylhäältä sulkeutuvalle prässille. Liitin kulkee pitkässä avoimessa kanavassa ennen puristusasemaa, joten liitinrivi on tuettu alasimen molemmilta puolilta ja pysyy linjassa indeksoitaessa eteenpäin. Nylonrengasversio käyttää erillistä istukkamuotoa, joka paikantaa eristyskauluksen irti puristeesta.

Se määritetään korvausmuotiksi, kun liitinperhe on jo määritelty olemassa olevassa JST-applikaattorissa, ja räätälöidyksi muotiksi, kun holkin mitat tai rengasistukka poikkeavat tavallisesta U-muodon alueesta.

Tärkeimmät ominaisuudet

1. OTP U-muotoinen muotti-istukka avoholkillisille liittimille, erillinen istukkamuoto esieristetyille nylonrengasliittimille

2. Vaaka- ja pystyversion puristus samalla rungolla ja kiinnityksellä

3. Pitkä avoin syöttökanava ennen puristusasemaa, tukee liitinriviä alasimen molemmin puolin

4. Jousivarsi ja irrotusvivusto sisääntulossa, pitävät liittimen linjassa sen saapuessa puristusasemaan

5. JST-liittimen puristuskoneen kiinnitys, suora vaihto applikaattoriasemalla

6. Muotin mitat tilauksesta liittimille, jotka ovat tavallisen U-muodon ja rengasalueen ulkopuolella

Tekniset tiedot

Parametri	Spesifikaatio
Malli	JW-AP12
Puristustyyppi	Vaaka- ja pystypuristus
Muottityyppi	OTP U-muotoinen muotti, esieristetty nylonrengastyyppi
Yhteensopivuus	JST-liittimen puristuskoneet
Sovellus	Liittimen puristusapplikaattori, liittimen puristinkone
Räätälöinti	Räätälöitävä liitinapplikaattorin muotti

Sovellukset

— JST-liittimen puristuskoneet, joissa ajetaan OTP U-muotoisia avoholkillisia liittimiä

— Esieristetyt nylonrengasliittimet puristettuna samalla applikaattoriasemalla

— Johtosarjalinjat, jotka puristavat rengasliittimiä, jatkoksia ja holkkeja samassa liitinperheessä

— Korvaus- tai toinen muotti, kun liitinpiirustus poikkeaa tavallisesta U-muodosta

— Pystyprässiasemat, joiden on pidettävä sama puriste kuin vaakalinjalla

PRODUCT | PARAMETERS

HOW TO MATCH THE MOLD BLADE OF THE TRANSVERSE TERMINAL

Transverse terminal 01

Transverse terminal : the axis direction of the terminal and the connecting terminal with an angle of 90 degrees





02 Transverse mold

The OTP transverse mold is the most commonly used mold in the wire harness processing industry. Its advantage lies in the ease of feeding and debugging. And the number of blades is small, easy to install. Equipped with two scale knobs to easily adjust the blade.



A TOTAL OF FOUR BLADES 03

Different terminals require different blades to crimp the terminals

Complete equipment display ▶

A pair of blades is provided on the mold, if you need more blades, you need to buy them separately



1.5Ton terminal machine

+



OTP Transverse mold

=




HOW TO MATCH THE MOLD BLADE OF
THE STRAIGHT SHAPE TERMINAL
STRAIGHT SHAPE TERMINAL
01
Straight terminal: a terminal with an angle of 0 degrees from the axial direction of the terminal.
02
STRAIGHT MOLD
The OTP straight mold knife set is composed of more than six blades. Four of them are conventional blades for riveting core wires and outer covers.
A TOTAL OF FOUR BLADES
03
Different terminals require different blades to crimp the terminals
Complete equipment display ▶
A pair of blades is provided on the mold, if you need more blades, you need to buy them separately
1.5Ton terminal machine
straight mold


HOW TO MATCH THE MOLD BLADE OF
THE SINGLE GRAIN MOULD
SINGLE TERMINAL
01
Single terminal: single terminal without connecting tape
02
SINGLE GRAIN MOULD
OTP single-grain molds are commonly used for crimping of single-grain pre-insulated terminals, ground terminals, spring-loaded terminals and other terminals. Installation and commissioning are extremely simple. Especially suitable for novice operations.
A TOTAL FO TWO BLADES
03
Different terminals require different blades to crimp the terminals
Complete equipment display ▶
A pair of blades is provided on the mold, if you need more blades, you need to buy them separately
1.5Ton terminal machine
Single grain mould

HOW TO MATCH THE MOLD BLADE OF THE SPECIAL TERMINAL

01 SPECIAL TERMINAL

Such as flag-shaped terminals, double-material terminals, terminals with material on the head of the terminal, etc.





02 CUSTOMIZED MOLD

After receiving the sample terminal, it is specially customized according to the terminal. 3-5 working days delivery

03 CUSTOM BLADE

Different terminals require different blades to crimp the terminals



PRODUCT | SIZE

TERMINAL MACHINE STRUCTURE





WANXIN, TAIWAN



RED WAVE SWITCH



ALLOY WEAR -RESISTANT HANGING HEAD


Four-point terminal machine display ▼
1.5Ton terminal machine
Four-point mold


TERMINAL MACHINE ACCESSORIES

六边形模具



四边形模具



上下B形冲压模



四点模具

